

law, except that, for the purposes of the present Convention "from the nearest land" of the north eastern coast of Australia shall mean from a line drawn from a point on the coast of Australia in

latitude 11° 00' South, longitude 142° 08' East to a point in
latitude 10° 35' South,
longitude 141° 55' East – thence to a point latitude 10° 00' South,
longitude 142° 00' East, thence to a point latitude 9° 10' South,
longitude 143° 52' East, thence to a point latitude 9° 00' South,
longitude 144° 30' East, thence to a point latitude 13° 00' South,
longitude 144° 00' East, thence to a point latitude 15° 00' South,
longitude 146° 00' East, thence to a point latitude 18° 00' South,
longitude 147° 00' East, thence to a point latitude 21° 00' South,
longitude 153° 00' East, thence to a point on the coast of Australia
in latitude 24° 42' South, longitude 153° 15' East.

(10) "Special area" means a sea area where for recognized technical reasons in relation to its oceanographical and ecological condition and to the particular character of its traffic the adoption of special mandatory methods for the prevention of sea pollution by oil is required. Special areas shall include those listed in Regulation 10 of this Annex.

(11) "Instantaneous rate of discharge of oil content" means the rate of discharge of oil in litres per hour at any instant divided by the speed of the ship in knots at the same instant.

(12) "Tank" means an enclosed space which is formed by the permanent structure of a ship and which is designed for the carriage of liquid in bulk.

(13) "Wing tank" means any tank adjacent to the side shell plating.

(14) "Centre tank" means any tank inboard of a longitudinal bulkhead.

(15) "Slop tank" means a tank specifically designated for the collection of tank drainings, tank washings and other oily mixtures.

(16) "Clean ballast" means the ballast in a tank which since oil was last carried therein, has been so cleaned that effluent therefrom if it were discharged from a ship which is stationary into clean calm water on a clear day would not produce visible traces of oil on the surface of the water or on adjoining shorelines or cause a sludge or emulsion to be deposited beneath the surface of the water or upon adjoining shorelines. If the ballast is discharged through an oil discharge monitoring and control system approved by the Administration, evidence based on such a system to the effect that the oil content of the effluent did not exceed 15 parts per million shall be determinative that the ballast was clean, notwithstanding the presence of visible traces.

(17) "Segregated ballast" means the ballast water introduced into a tank which is completely separated from the cargo oil and oil fuel system and which is permanently allocated to the carriage of ballast or to the carriage of ballast or cargoes other than oil or noxious substances as variously defined in the Annexes of the present Convention.

(18) "Length" (L) means 96 per cent of the total length on a waterline at 85 per cent of the least moulded depth measured from the top of the keel, or the length from the foreside of the stem to the axis of the rudder stock on that waterline, if that be greater. In ships designed with a rake of keel the waterline on which this length is measured shall be parallel to the designed waterline. The length (L) shall be measured in metres.

(19) "Forward and after perpendiculars" shall be taken at the forward and after ends of the length (L). The forward perpendicular shall coincide with the foreside of the stem on the waterline on which the length is measured.

(20) "Amidships" is at the middle of the length (L).