

graph (6) of this Regulation and an effective filtering system, complying with paragraph (7) of this Regulation.

(3) The Administration shall ensure that ships of less than 400 tons gross tonnage are equipped, as far as practicable, to retain on board oil or oily mixtures or discharge them in accordance with the requirements of Regulation 9(1)(b) of this Annex.

(4) For existing ships the requirements of paragraphs (1), (2) and (3) of this Regulation shall apply three years after the date of entry into force of the present Convention.

(5) An oil discharge monitoring and control system shall be of a design approved by the Administration. In considering the design of the oil content meter to be incorporated into the system, the Administration shall have regard to the specification recommended by the Organization.* The system shall be fitted with a recording device to provide a continuous record of the oil content in parts per million. This record shall be identifiable as to time and date and shall be kept for at least three years. The monitoring and control system shall come into operation when there is any discharge of effluent into the sea and shall be such as will ensure that any discharge of oily mixture is automatically stopped when the oil content of effluent exceeds that permitted by Regulation 9(1)(b) of this Annex. Any failure of this monitoring and control system shall stop the discharge and be noted in the Oil Record Book. The defective unit shall be made operable before the ship commences its next voyage unless it is proceeding to a repair port. Existing ships shall comply with all of the provisions specified above except that the stopping of the discharge may be performed manually.

(6) Oily-water separating equipment or an oil filtering system shall be of a design approved by the Administration and shall be such as will ensure that any oily mixture discharged into the sea after passing through the separator or filtering systems shall have an oil content of not more than 100 parts per million. In considering the design of such equipment, the Administration shall have regard to the specification recommended by the Organization.*

(7) The oil filtering system referred to in paragraph (2)(b) of this Regulation shall be of a design approved by the Administration and shall be such that it will accept the discharge from the separating system and produce an effluent the oil content of which does not exceed 15 parts per million. It shall be provided with alarm arrangements to indicate when this level cannot be maintained.

Regulation 17

Tanks for Oil Residues (Sludge)

(1) Every ship of 400 tons gross tonnage and above shall be provided with a tank or tanks of adequate capacity, having regard to the type of machinery and length of voyage, to receive the oily residues (sludges) which cannot be dealt with otherwise in accordance with the requirements of this Annex, such as those resulting from the purification of fuel and lubricating oils and oil leakages in the machinery spaces.

(2) In new ships, such tanks shall be designed and constructed so as to facilitate their cleaning and the discharge of residues to reception facilities. Existing ships shall comply with this requirement as far as is reasonable and practicable.

Regulation 18

Pumping, Piping and Discharge Arrangements of Oil Tankers

(1) In every oil tanker, a discharge manifold for connexion to reception facilities for the discharge of dirty ballast water or oil contaminated water shall be located on the open deck on both sides of the ship.

* Reference is made to the Recommendation on International Performance Specifications for Oily-Water Separating Equipment and Oil Content Meters adopted by the Organization by Resolution A. 233 (VII).