

(2) In every oil tanker, pipelines for the discharge to the sea of effluent which may be permitted under Regulation 9 of this Annex shall be led to the open deck or to the ship's side above the waterline in the deepest ballast condition. Different piping arrangements to permit operation in the manner permitted in sub-paragraphs (4)(a) and (b) of this Regulation may be accepted.

(3) In new oil tankers means shall be provided for stopping the discharge of effluent into the sea from a position on upper deck or above located so that the manifold in use referred to in paragraph (1) of this Regulation and the effluent from the pipelines referred to in paragraph (2) of this Regulation may be visually observed. Means for stopping the discharge need not be provided at the observation position if a positive communication system such as telephone or radio system is provided between the observation position and the discharge control position.

(4) All discharges shall take place above the waterline except as follows:

- (a) Segregated ballast and clean ballast may be discharged below the waterline in ports or at offshore terminals.
- (b) Existing ships which, without modification, are not capable of discharging segregated ballast above the waterline may discharge segregated ballast below the waterline provided that an examination of the tank immediately before the discharge has established that no contamination with oil has taken place.

#### Regulation 19

##### *Standard Discharge Connection*

To enable pipes of reception facilities to be connected with the ship's discharge pipeline for residues from machinery bilges, both lines shall be fitted with a standard discharge connection in accordance with the following table:

##### *STANDARD DIMENSIONS OF FLANGES FOR DISCHARGE CONNECTIONS*

Description	Dimension
Outside diameter	215 mm
Inner diameter	According to pipe outside diameter
Bolt circle diameter	183 mm
Slots in flange	6 holes 22 mm in diameter equidistantly placed on a bolt circle of the above diameter, slotted to the flange periphery. The slot width to be 22 mm
Flange thickness	20 mm
Bolts and nuts: quantity, diameter	6, each of 20 mm in diameter and of suitable length
The flange is designed to accept pipes up to a maximum internal diameter of 125 mm and shall be of steel or other equivalent material having a flat face. This flange, together with a gasket of oilproof material, shall be suitable for a service pressure of 6 kg/cm <sup>2</sup> .	

#### Regulation 20

##### *Oil Record Book*

(1) Every oil tanker of 150 tons gross tonnage and above and every ship of 400 tons gross tonnage and above other than an oil tanker shall be provided with an Oil Record Book,