

capacity of segregated ballast tanks shall be at least such that, in any ballast condition at any part of the voyage, including the conditions consisting of lightweight plus segregated ballast only, the ship's draughts and trim can meet each of the following requirements:

- (a) the moulded draught amidships (dm) in metres (without taking into account any ship's deformation) shall not be less than:
$$dm = 2.0 + 0.02 L;$$
- (b) the draughts at the forward and after perpendiculars shall correspond to those determined by the draught amidships (dm) as specified in sub-paragraph (a) of this paragraph, in association with the trim by the stern of not greater than 0.015 L; and
- (c) in any case the draught at the after perpendicular shall not be less than that which is necessary to obtain full immersion of the propeller(s).

(3) In no case shall ballast water be carried in cargo tanks except on those rare voyages when weather conditions are so severe that, in the opinion of the master, it is necessary to carry additional ballast water in cargo tanks for the safety of the ship. Such additional ballast water shall be processed and discharged in compliance with Regulation 9 of this Annex and in accordance with the requirements of Regulation 15 of this Annex and entry shall be made in the Oil Record Book referred to in Regulation 20 of this Annex.

(4) In the case of new crude oil tankers, the additional ballast permitted in paragraph (3) of this Regulation shall be carried in cargo tanks only if such tanks have been crude oil washed in accordance with Regulation 13 B of this Annex before departure from an oil unloading port or terminal.

(5) Notwithstanding the provisions of paragraph (2) of this Regulation, the segregated ballast conditions for oil tankers less than 150 metres in length shall be to the satisfaction of the Administration.

(6) Every new crude oil tanker of 20,000 tons deadweight and above shall be fitted with a cargo tank cleaning system using crude oil washing. The Administration shall undertake to ensure that the system fully complies with the requirements of Regulation 13 B of this Annex within one year after the tanker was first engaged in the trade of carrying crude oil or by the end of the third voyage carrying crude oil suitable for crude oil washing, whichever occurs later. Unless such oil tanker carries crude oil which is not suitable for crude oil washing, the oil tanker shall operate the system in accordance with the requirements of that Regulation.

Existing crude oil tankers of 40,000 tons deadweight and above

(7) Subject to the provisions of paragraphs (8) and (9) of this Regulation every existing crude oil tanker of 40,000 tons deadweight and above shall be provided with segregated ballast tanks and shall comply with the requirements of paragraphs (2) and (3) of this Regulation from the date of entry into force of the present Protocol.

(8) Existing crude oil tankers referred to in paragraph (7) of this Regulation may, in lieu of being provided with segregated ballast tanks, operate with a cargo tank cleaning procedure using crude oil washing in accordance with Regulation 13 B of this Annex unless the crude oil tanker is intended to carry crude oil which is not suitable for crude oil washing.

(9) Existing crude oil tankers referred to in paragraph (7) or (8) of this Regulation may, in lieu of being provided with segregated ballast tanks or operating with a cargo tank cleaning procedure using crude oil washing, operate with dedicated clean ballast tanks in accordance with the provisions of Regulation 13 A of this Annex for the following period:

- (a) for crude oil tankers of 70,000 tons deadweight and above, until two years after the date of entry into force of the present Protocol; and
- (b) for crude oil tankers of 40,000 tons deadweight and above but below 70,000 tons deadweight, until four years after the date of entry into force of the present Protocol.