

- (b) agreement has been reached between the Administration and the Governments of the Port States referred to in sub-paragraph (1)(a) or (b) of this Regulation concerning the use of an existing oil tanker for a specific trade;
- (c) the adequacy of the reception facilities in accordance with the relevant provisions of this Annex at the ports or terminals referred to above, for the purpose of this Regulation, is approved by the Governments of the States Parties to the present Protocol within which such ports or terminals are situated; and
- (d) the International Oil Pollution Prevention Certificate is endorsed to the effect that the oil tanker is solely engaged in such specific trade.

(3) Every oil tanker engaged in a specific trade shall be provided with a Supplement to the Oil Record Book referred to in Regulation 20 of this Annex as set out in Supplement 3 to Appendix III of this Annex. The Supplement shall be permanently attached to the Oil Record Book.

#### Regulation 13 D

##### *Existing Oil Tankers Having Special Ballast Arrangements*

(1) Where an existing oil tanker is so constructed or operates in such a manner that it complies at all times with the draught and trim requirements set out in Regulation 13(2) of this Annex without recourse to the use of ballast water, it shall be deemed to comply with the segregated ballast tank requirements referred to in Regulation 13(7) of this Annex, provided that all of the following conditions are complied with:

- (a) operational procedures and ballast arrangements are approved by the Administration;
- (b) agreement is reached between the Administration and the Governments of the Port States Parties to the present Protocol concerned when the draught and trim requirements are achieved through an operational procedure; and
- (c) the International Oil Pollution Prevention Certificate is endorsed to the effect that the oil tanker is operating with special ballast arrangements.

(2) In no case shall ballast water be carried in oil tanks except on those rare voyages when weather conditions are so severe that, in the opinion of the master, it is necessary to carry additional ballast water in cargo tanks for the safety of the ship. Such additional ballast water shall be processed and discharged in compliance with Regulation 9 of this Annex and in accordance with the requirements of Regulation 15 of this Annex, and entry shall be made in the Oil Record Book referred to in Regulation 20 of this Annex.

(3) An Administration which has endorsed a Certificate in accordance with sub-paragraph (1)(c) of this Regulation shall communicate to the Organization the particulars thereof for circulation to the Parties to the present Protocol.

#### Regulation 13 E

##### *Protective Location of Segregated Ballast Spaces*

(1) In every new crude oil tanker of 20,000 tons deadweight and above and every new product carrier of 30,000 tons deadweight and above, the segregated ballast tanks required to provide the capacity to comply with the requirements of Regulation 13 of this Annex which are located within the cargo tank length, shall be arranged in accordance with the requirements of paragraphs (2), (3) and (4) of this Regulation to provide a measure of protection against oil outflow in the event of grounding or collision.

(2) Segregated ballast tanks and spaces other than oil tanks within the cargo tank length ( $L_t$ ) shall be so arranged as to comply with the following requirement:

$$\Sigma PA_c + \Sigma PA_s \geq J[L_t (B + 2D)]$$